

The logo for Arctek, featuring the word "arctek" in a stylized font. The "ar" is in red and the "ctek" is in blue. A red and blue arc is positioned above the letters.

OVERLAY PERFORMANCE TECHNOLOGY

BY Arclin

Guard™



Description

Arctek® proprietary technology was used to create Guard™ overlay. It creates the smoothest, moisture resistant surface, even on rough or unsanded substrates. Arctek's primer coating can be painted with regular, external paint systems making any colour or gloss level achievable. For outdoor applications, Guard™ overlay protects panels for up to six months without the need to apply a topcoat.

Features

- Superior masking of defects in wood based panels
- Consistently smooth paint results
- Moisture ingress protection
- Perfect compatibility with regular external paint systems (see our product datasheet)

Benefits

- Fused to the panel protecting it against moisture ingress
- No need to hurry your paint job, Guard™ protects against the elements
- No repair of defects in the wood based panel necessary
- Clean Guard™ with regular household products
- Adds lifetime to your paint system and extends design life of the wood based panel substrate



Paintable



Textures to
match your needs



Moisture
resistance



Weather
protection



Strength
& durability

Guard™ Applications



Fascias & Soffits



Exterior Decorative



Doors



General Purpose

System Suppliers

Arctek® Technology by Arclin, the performance overlay solution for timber manufactured building materials is now available in the UK and Europe. In the System Suppliers section of our website (arctek.arclin.com) we provide an up-to-date list of panel manufacturers and processors using Arctek® overlay performance technology. You can also always reach out to us at enquiries.arctek@arclin.com



The information and recommendations contained herein are offered as a service to our customers but are not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to the safe handling and use of these materials. The information and recommendations provided herein were believed by ARCLIN to be accurate at the time of preparation or obtained from sources believed to be generally reliable. However, ARCLIN makes no warranty concerning their accuracy and ARCLIN will not be liable for claims relating to any party's use of or reliance on information or recommendations contained herein regardless of whether it is claimed that the information or recommendations are inaccurate, incomplete or otherwise misleading.

EU-02.22

arctek.arclin.com

OVERLAY PERFORMANCE TECHNOLOGY